Datasheet

ML26 Accent Light



Type:

MODULINE Linear System Inset MLA4-9302007F-BB

General

- Indoor
- Accent Light
- Fixed
- Profile Inset
- Version: square
- Housing: black
- Reflector: black
- System Output: 550lm
- IP 20

LED

OSRAM

- 3000K
- CRI90
- 750lm
- 50000h@L80B10
- SDCM: 3

Optics

- Beam angle: 20°
- UGR <19

Electric

- LED Driver: ON-OFF
- LED Power: 6W
- System Power: 7W
- 48V


Dimensions

- Measurement: 194mm x 22mm
- Height: 43mm


Description

MODULINE 26 Linear System Accent Light Inset with ON-OFF; black painted finish (RAL 9005) and black reflector; LED 6W; measurement 194mm x 22mm; height of the profile inset 43mm; CCT 3000K with an LED Output of 750lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; precise beam characteristic with 20° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)

Light distribution



Technical drawing



Driver

Б СВ СЕ вонз

