## Datasheet

# ML26 Spotlight



Type:

#### MODULINE Linear System Inset MLR1-9271805F-BB

#### General

- Indoor
- Spotlight
- Adjustable
- Profile Inset
- Version: round
- Housing: black
- Reflector: black
- System Output: 330lm
- IP 20

LED

### **OSRAM**

- 2700K
- CRI90
- 420lm
- 50000h@L80B10
- SDCM: 3

#### Optics

- Beam angle: 18°
- UGR <19

#### Electric

- LED Driver: ON-OFF
- LED Power: 4W
- System Power: 5W
- 48V


#### Dimensions

- Measurement: Ø25mm
- Height: 40mm


#### Description

MODULINE 26 Linear System Spotlight Inset with ON-OFF; black painted finish (RAL 9005) and black reflector; LED 5W; measurement Ø25mm; height of the spotlight is 40mm; wide of the profile inset is 190mm; CCT 2700K with an LED Output of 420lm; high color rendering at an index of CRI90; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; precise beam characteristic with 18° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)

#### Light distribution



#### **Technical drawing**



В СЕ Воня



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.