

DHI-VTNS2003B-2

2-wire Switch




- Supports 10-level cascade through the 2-wire port
- Supports connecting to 20 indoor monitors and 2 door stations
- Supports connecting through RJ45 port


Technical Specification		
Basic		
Status Indicator Light	4	
Communication Mode	2-wire	
Cascade Ability	10	
Port		
port	Two 2-wire ports for cascade	
port	Two RJ45 ports, 10 Mbps/100 Mbps Ethernet	
port	One 2-wire device port	
General		
Casing	PC + ABS	
Appearance color	White	
Power Supply	DC 48V, 1A-3A	
Power Adapter	Optional	
Installation	Guide rail mount	
Certifications	CE; FCC; UL	
Accessory	Power converter cable	
Product Dimensions	131.1 mm × 103 mm × 40 mm (5.16" × 4.06" × 1.57")	
Operating Temperature	-10°C to +55°C (14°F to 131°F)	
Operating Humidity	10%–95% (RH, non-condensing)	

Operating Altitude	0-3000 m
Power Consumption	≤ 15W (KIT)
Net Weight	0.25 kg (0.55lb)
Gross Weight	0.39 kg (0.86 lb)

Ordering Information			
Туре	Model	Description	
2-wire Switch	DHI-VTNS2003B-2	2-wire Switch	
Accessories	ADS-65LSI-52-1 48060G	Power supply finished product- AC/DC power adapter-DC power adapter-AC100V~240V-48V1.25A-VI- Φ6.5×Φ1.35×10	
	EDP-240-48	Power supply finished product-AC/ DC certified power supply-Power supply-AC100V~240V-48V5A	

Dimensions (mm[inch])





Application

